

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION 5 77 WEST JACKSON BOULEVARD CHICAGO, IL 60604-3590

PAGE 1 of 13

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY (USEPA) UNDERGROUND INJECTION CONTROL MINOR PERMIT MODIFICATION: CLASS II

Permit Number: MI-073-2D-0009

Facility Name: Fred Beutler #2

Pursuant to the provisions of the Safe Drinking Water Act, as amended (42 U.S.C. §300f <u>et seq.</u>, commonly known as the SDWA) and implementing regulations promulgated by the USEPA at Parts 124, 144, 146 and 147 of Title 40 of the Code of Federal Regulations (40 CFR),

Summit Petroleum Corporation of Mt. Pleasant, Michigan

is hereby authorized to operate an existing injection well located in Michigan, Isabella County, T15N, R6W, Section 33, NE 1/4 Section, for injection into the Dundee Limestone at depths between 3707 feet and 3868 feet, upon the express condition that the permittee meet the restrictions set forth herein.

The purpose of the injection is limited to noncommercial brine disposal from production wells owned or operated by Summit Petroleum Corporation.

All references to Title 40 of the Code of Federal Regulations are to all regulations that are in effect on the date that this permit is effective.

This permit is a minor modification of an existing permit, which was signed on March 30, 1987. This permit shall become effective on 111 12 2006 and shall remain in full force and effect during the operating life of the well, unless this permit is otherwise revoked, terminated, modified or reissued pursuant to 40 CFR §§144.39, 144.40 or 144.41. This permit shall also remain in effect upon delegation of primary enforcement responsibility to the State of Michigan, unless that State chooses to adopt this permit as a State permit. This permit will be reviewed at least every 5 years from the effective date specified above.

Signed and dated:

Jo Lynn Traub

Director, Water Division

A. EFFECT OF PERMIT

The permittee is allowed to engage in underground injection-in accordance with the conditions of this permit. The underground injection activity, otherwise authorized by this permit or rule. shall not allow the movement of fluid containing any contaminant into underground sources of drinking water, if the presence of that contaminant may cause a violation of any Primary Drinking Water Regulation pursuant to 40 CFR Part 142 or may otherwise adversely affect the health of persons. Any underground injection activity not specifically authorized in this permit or otherwise authorized by permit or rule is prohibited. Issuance of this permit does not convey property rights of any sort or any exclusive privilege; nor does it authorize any injury to persons or property, any invasion of other private rights, or any infringement of State or local law or regulations. Compliance with the terms of this permit does not constitute a defense to any action brought under Section 1431 of the Safe Drinking Water Act (SDWA), or any other law governing protection of public health or the environment, for any imminent and substantial endangerment to human health or the environment.

B. PERMIT ACTIONS

This permit may be modified, revoked and reissued, or terminated for cause as specified in 40 CFR §144.39, §144.40, and §144.41. The filing of a request for a permit modification, revocation and reissuance, termination, or the notification of planned changes or anticipated noncompliance on the part of the permittee does not stay the applicability or enforceability of any permit condition.

C. SEVERABILITY

The provisions of this permit are severable, and if any provision of this permit or the application of any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances and to the remainder of this permit shall not be affected thereby.

D. CONFIDENTIALITY

In accordance with 40 CFR Part 2 and §144.5, any information submitted to USEPA pursuant to this permit may be claimed as confidential by the submitter. Any such claim must be asserted at the time of submission by stamping the words "confidential business information" on each page containing such information. If no claim is made at the time of submission, USEPA may make the information available to the public without further notice. If a claim is asserted, the validity of the claim will be assessed in accordance with the procedures in

40 CFR Part 2 (Public Information). Claims of confidentiality for the following information will be denied:

- 1) The name and address of the permittee; and
- 2) Information which deals with the existence, absence or level of contaminants in drinking water.

E. DUTIES AND REQUIREMENTS

- 1. Duty to Comply The permittee shall comply with all conditions of this permit, except to the extent and for the duration such noncompliance is authorized by an emergency permit. Any permit noncompliance constitutes a violation of the SDWA and is grounds for enforcement action, permit termination, revocation and reissuance or modification.
- 2. Need to Halt or Reduce Activity not a Defense It shall not be a defense for a permittee in an enforcement action to state that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
- 3. <u>Duty to Mitigate</u> The permittee shall take all reasonable steps to minimize or correct any adverse impact on the environment resulting from noncompliance with this permit.
- 4. Proper Operation and Maintenance The permittee shall at all times properly operate and maintain all facilities. Proper operation and maintenance includes effective performance and adequate funding, including appropriate quality assurance procedures.
- 5. Duty to Provide Information The permittee shall furnish to the Director, within thirty (30) days, any information which the Director may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The permittee shall also furnish to the Director, upon request, copies of records required by this permit to be retained.
- 6. Inspection and Entry The permittee shall allow the Director, or an authorized representative, upon the presentation of credentials and other documents as may be required by law to:
 - (a) Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records are kept under the conditions of this permit;

- (b) Have access to and copy, at reasonable times, any records that must be retained under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring equipment), practices, or operations, regulated or required under this permit; and
- (d) Sample or monitor the injected fluids, at reasonable times, for the purposes of assuring permit compliance, or as otherwise authorized by the SDWA, at any location.

7. Records

- (a) The permittee shall retain records and all monitoring information, including all calibration and maintenance records required by this permit, for a period of at least five (5) years from the date of the sample, measurement or report. The permittee shall maintain records of all data required to complete this permit application and any supplemental information submitted under 40 CFR §144.27, §144.28 and §144.31. These periods may be extended by request of the Director at any time.
- (b) The permittee shall retain records concerning the nature and composition of all injected fluids until three (3) years after the completion of plugging and abandonment in accordance with the plugging and abandonment plan, contained in Attachment A of this permit. At the conclusion of the retention period, if the Director so requests, the permittee shall deliver the records to the Director.
- (c) Records of monitoring information shall include:
 - (i) The date, exact place, and the time of sampling or measurements;
 - (ii) The individual(s) who performed the sampling or measurements:
 - (iii) A precise description of both sampling methodology and the handling of samples;
 - (iv) The date(s) analyses were performed;
 - (v) The individual(s) who performed the analyses;
 - (vi) The analytical techniques or methods used; and
 - (vii) The results of such analyses.

8. <u>Notification Requirements</u>

- (a) Planned Changes The permittee shall notify the Director at least thirty (30) days prior to any planned physical alterations or additions to the permitted facility, or changes in the injection fluids. An analysis of the new injection fluids shall be submitted to the Director in accordance with Permit Conditions (G)(2) and (G)(3).
- (b) <u>Commencing Injection</u> The permittee shall not commence injection until construction is complete and any remedial procedures described in Attachment B are complete, and;
 - (i) The permittee has submitted a report on the remedial work to the Director; and
 - (ii) The Director has inspected or otherwise reviewed the remedial work and notified the permittee in writing that he or she is in compliance with the conditions of this permit.
- 9. Anticipated Noncompliance The permittee shall give advance notice to the Director of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.
- 10. Transfer of Permits This permit is not transferrable to any person except after notice is sent to the Director and the requirements of 40 CFR §144.38 have been met. The Director may require modification or revocation of the permit to change the name of the permittee and incorporate such other requirements as may be necessary under the SDWA.
- 11. Compliance Schedules Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than thirty (30) days following each schedule date.

12. Twenty-Four (24) Hour Reporting

(a) The permittee shall report to the Director any noncompliance which may endanger health or the environment. This information shall be provided orally within twenty-four (24) hours from the time the permittee becomes aware of the circumstances, and shall include the following as information:

- (i) Any monitoring or other information which indicates that any contaminant may cause an endangerment to an underground source of drinking water; or _____
- (ii) Any noncompliance with a permit condition or malfunction of the injection system which may cause fluid migration into or between underground sources of drinking water.
- (b) A written submission shall also be provided as soon as possible but no later than five (5) days from the time the permittee becomes aware of the circumstances. The written submission shall contain a description of the noncompliance and its cause; the period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance.
- 13. Other Noncompliance The permittee shall report all other instances of noncompliance. The reports shall contain the information listed in Permit Condition (E)(12)(b).
- 14. Other Information If or when the permittee becomes aware that he or she failed to submit any relevant facts in the permit application, or submitted incorrect information in a permit application or in any report to the Director, the permittee shall promptly submit such facts or corrected information.
- 15. Signatory Requirements All reports or other information requested by the Director shall be signed and certified according to 40 CFR \$144.32.
- 16. Notice of Plugging and Abandonment The permittee shall notify the Director at least thirty (30) days before conversion or abandonment of the well.
- Plugging and Abandonment The permittee shall plug and abandon the well as provided in the plugging and abandonment plan contained in Attachment A of this permit. After a cessation of operation of two years, the owner or operator shall plug and abandon the well in accordance with the plan provided in Attachment A unless the operator fulfills the other requirements under 40 CFR §144.52(a)(6). The permittee shall notify the Director of plugging and abandonment in accordance with the reporting procedures in Permit Condition (G)(3)(d).
- 18. Financial Responsibility The permittee shall maintain financial responsibility and resources to plug and abandon the underground

injection well in accordance with 40 CFR §144.52(a)(7). The permittee shall not substitute an alternative demonstration of financial responsibility from that which the Director has approved, unless he or she has previously submitted evidence of that alternative demonstration to the Director and the Director has notified him or her in writing that the alternative demonstration of financial responsibility is acceptable.

19. Insolvency

- (a) In the event of the bankruptcy of the trustee or issuing institution of the financial mechanism, or a suspension or revocation of the authority of the trustee institution to act as trustee or the institution issuing the financial mechanism to issue such an instrument, the permittee must submit an alternative demonstration of financial responsibility acceptable to the Director within sixty (60) days after such event.
- (b) An owner or operator must also notify the Director by certified mail of the commencement of voluntary or involuntary proceedings under Title 11 (Bankruptcy), U.S. Code, naming the owner or operator as debtor, within ten (10) business days after the commencement of the proceeding. A guarantor of a corporate guarantee must make such a notification if he or she is named as debtor, as required under the terms of the guarantee.

20. Remedial Action

- (a) The permittee shall comply with the remedial action plan contained in Attachment B of this permit.
- (b) The permittee shall not commence injection until all remedial action has been taken in accordance with the plan contained in Attachment B and the requirements in Permit Condition (E)(8)(b) have been met.

21. Mechanical Integrity

- (a) The permittee must provide a mechanical integrity demonstration, in accordance with 40 CFR §146.8, within thirty (30) days of the effective date of this permit, unless mechanical integrity was demonstrated for the injection well after June 25, 1984.
- (b) A demonstration of mechanical integrity, in accordance with 40 CFR §146.8, shall be performed every five (5) years from the effective date of the last approved demonstration.

The permittee may continue operation only if the permittee has received written notice from the Director that such demonstration is satisfactory. The permittee shall notify the Director of his or her intent to demonstrate mechanical integrity at least thirty (30) days prior to such demonstration. In addition to the five (5) year demonstration, the Director has the authority to require the permittee to conduct a demonstration of the mechanical integrity of the well at any time.

- (c) All gauges used in mechanical integrity demonstrations shall be calibrated according to the National Bureau of Standards methods and be accurate to within 0.5% of full scale initially and annually thereafter. A copy of the calibration certificate shall be submitted to the Director on an annual basis.
- (d) The permittee shall cease injection if a loss of mechanical integrity as defined by 40 CFR §146.8 becomes evident during operation. Operations shall not be resumed until the permittee has complied with the provisions of this permit regarding mechanical integrity demonstration and testing.
- (e) The permittee shall notify the Director of the loss of mechanical integrity, in accordance with the reporting procedures in Permit Condition (G)(3)(d).
- 22. Restriction on Injected Substances The permittee shall not inject any hazardous substances, per 40 CFR Part 261, at any time during the operation of the facility, and further, no substances other than those noted in the permit application shall be injected.

F. CONSTRUCTION REQUIREMENTS

- 1. Casing and Cementing Injection wells shall be cased and cemented to prevent the movement of fluids into or between underground sources of drinking water. The casing and cement used in the construction of the well are contained in Attachment C.
- 2. Tubing and Packer Specifications Injection shall only take place through tubing with a packer set within the casing at the bottom of the long string casing. Tubing and packer specifications shall be as represented in engineering drawings contained in Attachment C of this permit. Any proposed changes shall be submitted by the applicant for the approval of the Director before installation.

- 3. Wellhead Specifications For every injection well, the operator shall provide a one-fourth (1/4) to one-half (1/2) inch female fitting, with cut-off valve, to the tubing at the wellhead so that the amount of injection pressure being used may be measured by a representative of the USEPA by attaching a gauge having a one-fourth (1/4) to one-half (1/2) inch male fitting.
- 4. Formation Data Data on the injection and confining zones are contained in Attachment D of this permit.
- G. OPERATING, MONITORING AND REPORTING REQUIREMENTS
 - Operating Requirements
 - (a) Injection Pressure Limitation
 - (i) Beginning on the effective date of this permit, the permittee is authorized to operate the injection well, subject to the limitations and monitoring requirements set forth herein. The injection pressure and injected fluid shall be limited and monitored as specified in Attachment E.
 - (ii) Injection at a pressure which initiates fractures in the confining zone or causes the movement of injection or formation fluids into or between underground sources of drinking water is prohibited.
 - (iii) Injection between the outermost casing protecting underground sources of drinking water and the well bore is prohibited.
 - (iv) The annulus between the tubing and the long string casing shall be filled with a fluid approved by the Director. A positive pressure shall be maintained on the annulus.

2. Monitoring Requirements

(a) Samples and measurements taken for the purpose of monitoring shall be representative of the monitored activity. Grab samples shall be used to obtain a representative sample of the fluid to be analyzed. Attachment E describes the sampling location and required parameters for injection fluid analysis.

- (b) Analytical Methods Monitoring of the nature of injected fluids shall comply with applicable analytical methods cited and described in Table I of 40 CFR §136.3 or in Appendix III of 40 CFR Part 261 or by other methods that have been approved by the Director.
- (c) <u>Injection Fluid Analysis</u> The nature of the injection fluids shall be monitored quarterly for the parameters specified in Attachment E, except that specific gravity shall be monitored monthly. An initial analysis of the injection fluid is contained in Attachment E.
- (d) Injection Pressure, Annulus Pressure, Flow Rate and Cumulative Volume Injection pressure, annulus pressure, flow rate and cumulative volume shall be recorded at least weekly. All gauges used in monitoring shall be calibrated in accordance with Permit Condition (E)(21)(c).
- 3. Reporting Requirements Copies of the monitoring results and all other reports shall be submitted to the Director at the following address:

U.S. Environmental Protection Agency Region V 77 W. Jackson Boulevard Chicago, Illinois 60604 Attn: WU-16J

- (a) Monthly Reports Monitoring results obtained during each week shall be recorded on a form similar to that contained in Attachment F. Forms shall be submitted at the end of each month and shall be postmarked no later than the 10th day of the month following the sampling period. The first report shall be sent no later than the 10th day of the month following the month in which injection commences. This report shall include the weekly measurements of injection pressure, annulus pressure, flow rate and cumulative volume, and monthly measurements of the specific gravity of the injected fluids as required in Attachment E.
- (b) Quarterly Reports Monitoring results obtained each quarter shall include the measurements of injected fluid characteristics as required in Attachment E.
- (c) After one year from commencement of injection, the permittee may request a change in the frequency of monitoring if the permittee can demonstrate that there has not been and will not be significant variation in the information generated.

- (d) Reports on Well Tests, Workovers, and Plugging and Abandonment The applicant shall provide the Director with the following reports and test results within sixty (60) days of completion of the activity:
 - (i) Mechanical integrity tests;
 - (ii) Logging or other test data;
 - (iii) Well workovers (using EPA Form 7520-12 in Attachment F), and
 - (iv) Plugging and abandonment

H. PENALTIES FOR VIOLATIONS OF PERMIT CONDITIONS

Any person who operates this well in violation of permit conditions is subject to civil penalties, fines, and other enforcement action under the SDWA and may be subject to such actions under the Resource Conservation and Recovery Act. Any person who willfully violates permit condition may be subject to criminal prosecution.

ATTACHMENT A

OMB No. 2040-0042

Approval Expires 4/30/07

United States Environmental Protection Agency Washington, DC 20460 PLUGGING AND ABANDONMENT PLAN														
Name and	Address of Fa	cility						_	ss of Owner/		,,,,,			
FRED I	E BEUTLER MAN TWP IS		UNTY, MI		Meri kang a jeunggapiki erus gipgunjana) p		SUN	MMIT PET	ROLEUM MT PLEAS	CORPORA				
Loo	ate Well and Ou	rtline Unit on	- The state of the		State	State County					Permit Number			
	ate wen and Ot tion Plat - 640 A			Michigan	1		Isa	bella		MI4741/MI073 2D0009				
		N		Surface Lo	cation De	scr	iption							
	1 1 1		SW 1/4 of nW 1/4 of ne 1/4 of 1/4 of Section 33					Township 15n Range 6w						
	 		Locate well in two directions from nearest lines of quarter section and drilling unit Surface											
-	 - - -	_			Location 330 ft. frm (N/S) S Line of quarter section and 330 ft. from (E/W) W Line of quarter section.									
w	4-1-1		E					HORIZATION	N			CTIVITY		
 	<u> </u>				Area	idual Peri	mit			│				
			. !		Rule						rine Disposa	ı		
	T- T-					4	*******	esering		ومعمو	nhanced Red			
					Number	of Wells		أسي		1,000,00	Hydrocarbon Storage			
					pammining		opportunities and the second superior of the second second second second second second second second second se	ar ar mala or mary are not a requirement of	CLAS	ASS III				
		S		· Trefoonskipalitörikvi	Lease Nar	re FRED	E	BEUTLER		Well Numb	er #2	Stranger		
	CAS	SING AND TUBI	NG RECORD	AFTER	PLUGGING	•			METHO	OD OF EMPL	ACEMENT O	F CEMENT PI	-UGS	
SIZE	WT (LB/FT)	TO BE PUT IN	WELL (FT)	TO BE	LEFT IN W	ELL (FT)	Н	OLE SIZE	✓ The	Balance Me	thod			
10	41#	Orania II ray garage agent of the say it seems a		605		en e	The Dump Bailer Method							
6.625	17#	The trade of the same of the s		1747	bende de spiese bende al l'alliande en des d'en deserta. Distration au mallier de mais autris de l'alliande en de l'Alliande				The	Two-Plug M	lethod			
5.5	[15#]	percent and the second second second second second second		3707		ner programmy major direct Ty	Patricia	A CONTRACTOR OF THE PROPERTY O	Other					
أسيسهم	Expension to the particular design and	And a state of the party and a complete to the product of the party of		Equi e Marque Orpos	All and the second control of the second of									
	CEMENTING	TO PLUG AND	ABANDON D	ATA:		PLUG #1	1	PLUG #2	PLUG #3	PLUG #4	PLUG #5	PLUG #6	PLUG #7	
	lole or Pipe in v			(inche		4" O.H.		5.5	6.625	per called and all companies comments and	Salata Park Company Chair code	political programme and the second		
	Bottom of Tub	 _			*	3868	_	3700	1530	Decountry of the Editor of the State of	Principle of the second	Parties and the second and a second	Paleston increase on with or of	
<u> </u>	f Cement To Be		(g)			21		40	265	Service of the Servic	Temporal programme and constitution	Stanceschemical enterior engine and	Francisco constitution and	
i	olume To Be Pu					1.18cuf	-	1.18cuft	1.18cuft				Separate services and the services and t	
<u></u>	ed Top of Plug	······	***************************************			3700		3400	4	Charles and the second	Front state Schoolspace to the contribution of	TOWNSHIP CHICK HOUSE STREET PROPERTY.	Particular and processing and Tables	
	Vt. (Lb./Gal.)	ii tagged it.				3700		3400 15.6	surface	Programma			E	
	ment or Other N	Material (Class I	10)			15.6 CL/A		CL/A	CL/A	Constitution described to the constitution of	Control and the second control of the second	Encountry line resident reservoir	Processor and a second	
.,,,,,		T ALL OPEN H		DEDEC	DATED INT	Charles the Control of the Control o	100000			SING MILL D	F VADIED /:	anud	U	
ļ	From	, ALL OFEN R	CLL AND/OR	T		ERVALS A	מאח	MIERVALS	From	OUAC AAITT D	r AVIAIED (II	To		
140" 0	h. 3707	THE A P. LEW SHAPE, SPICE STREET, SPICE STRE	3868								and the same of th		Water III a William Water	
17.0 0.	The second of the second secon		Print and and and and and	- Sejind kapitungi natunaka Arak	where any constitution requirements	CONTRACTOR OF THE STREET	and to the con-	to he change of the change of the change of	e plane, mira pak, min al que que de la biscolo que ma	and the same of th	Egyptypistereseriacji pakarenisterjevisteria (majatika) pakarenisteria (majatika) (majat			
Description of the second	s a new person productioning different formers that we seem to be a second of the second	erarrament nagraphic organisation properties and resemble to the second			C. In case of the contract of			THE STREET STREET, STREET STREET, STRE	and assumed the production of the same	a, Cialiting at alpha at the first and property of the				
harmen to the other	and the first state of the stat	TO THE REAL PROPERTY OF THE PR	A CONTRACTOR DE	Control control and control of the control	Efficiency and Coulomback and Coulom	STATE OF THE STATE	SEPTIMENT.	COLUMN TO STATE OF THE PARTY OF	- PORT OF THE PROPERTY OF T	The second secon	TOTAL STREET,	The state of the s	The second secon	
Estimat	ed Cost to Plug	Wells		The state of the s	THE PETERSON AND ANY ANY ANY	perculations of sections	errendi. be		COLUMN TO SERVICE SERVICES CONTRACTOR CONTRA	ngt annihile di carini e record			men and the experience of the about the	
Ten T	housand Dolla	ars (\$10,000.00))	The Visit And And History of Street, and Andrews	mag ka ki ti ba sagaka da ing mang kanaman di ga da kanaman di	I AGOSTANIA NE TENESTE FANCES (FESSO	esseria e una	rissionalistissiidensi sitemin 11-44 ennassainkus	(so ya shina noshilad misakili mjeye (ji unmulo) / k	Elizario sistembri de la silva approvincia de la ligitacia (spira)	тр., колі калекціна (рефакція	lings make this transfer will small subsequences the si	**************************************	
a ir	Certification I certify under the penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the													
	ossiblilty of fin		-	40 CFR										
F	nd Official Title		or print)		Sig	nature	1	1 ~ <	111	0	\sim 0	Date Signe	}	
Rober	t J Long Pres	ident	and the state of t	sample or the party		L00		CA)	27	T	1	06/05/200	6	
EPA Fo	EPA Form 7520-14 (Rev. 8-01)													


6.00 P. 10 P			· · · · · · · · · · · · · · · · · · ·		
ORIGINAL WELL CONSTRUCTION	D VIG OPERATION	PLUGGING AE	SANDONMENT CONSTRUCTION		
			MI-073-2D-0009		
Fred E. Beutler #2			Page A-3 of 3		
PERMIT NO. 4741/ MI073 - 2D - 0019					
		·	,		
·	Surface -		Surface -		
		Top Plug Interval			
		4'-1530			
Top of cement					
Surface Surface					
	Surface Casing		Surface Casing		
	10" @ 605'		605'		
		*USDW Base Plug			
1 1 1 1 1 1		Interval	USDW Base		
		N/A	1480'		
Top of cement		*Intermediate Cut/Rip	*Intermediate		
Surface		Point Plug Interval	Cut/Rip Depth		
	Intermediate Csg.	*Third Plug Interval	*Intermediate Csg.		
	6.625" @ 1747	N/A	1747		
		*Middle Plug Interval			
		3400' - 3700'			
		*Long String Cut/Rip	*Long String Csg		
Top of Cement	Ŷ	Point Plug Interval	Cut/Rip Depth		
Surface	Packer Depth				
	3600′				
		Bottom Plug Depth	Long String Csg.		
Perforations	Long String Csg.	3700' - 3868'	3707'		
OH	5-1/2" @ 3707	*Mechanical Plug Depth			
Hole Size	* Depth	wechanical riug Depth	Depth		
6-1/4"	3868'		3868'		
** Add Any Additional Information		** Add Any Additional Information			
* May not Apply		* May not Apply			
LIST OF ALL OPEN AND/OR F	PERFORATED INTERVALS	AND INTERVALS WHERE C	ASING WILL BE VARIED		
Specify Open Hole/ Perforations/ Varied Casing	From	То	Formation Name		
Open Hole	3707'	3868'	Dundee		
	ro _{ng di} pangan dikir didiken pilikip palaman kanan mada kanan dikir didikan manyin kebupatan sebah				

ATTACHMENT B


Remedial Action Plan

Should upward fluid migration occur through the well bore of any previously unknown, improperly plugged or unplugged well in the area of review due to injection of permitted fluids, injection will be shut-in until proper plugging can be accomplished. Any flowage from such undiscovered wells will be considered noncompliance with this permit. Should any problem develop in the casing of the injection well, injection will be shut-in until such repairs can be made as to remedy the situation.

ATTACHMENT C



T D of well is 3868 ft.



ATTACHMENT D

Geological Data on Injection and Confining Zones

In Sherman Twp..., the Dundee is overlain by the Bell Shale and underlain by anhydrite of the Detroit River group. The top of the Dundee occurs at a depth of +- 3710 feet and has a thickness +-203 feet. The Dundee formation is composed of gray to brown limestone.

The interval in which brine water will be disposed of occurs +-2 ft. from the top of the Dundee zone, from 3712 - 3913 ft.

The zone is confined at the top by tightly packed limestone and Bell Shale. The lower part of the zone is confined at the bottom by the loss of porosity by the infilling of vugs with calcite and dolomite cement, this becomes the anhydrite of the Detroit River Group.

ATTACHMENT E

١

OPERATING, MONITORING AND REPORTING REQUIREMENTS

	LIMITATION	MINIMUM MONITORING	REQ.	MINIMUM REPORTING REQUIREMENTS
Characteristic	Maximum	Freq.	Type	
*Injection Pressure	912.0 psig	weekly		monthly
Annulus Pressure		weekly		monthly
Flow Rate		weekly		monthly
Cumulative Volume		weekly .		monthly '
Specific Gravity		monthly	grab	monthly
**Chemical Composition of	Injected Fluid	quarterly	grab	quarterly
Total Dissolved Solids		quarterly	grab	quarterly
рӉ		quarterly	grab	quarterly
Resistivity, ohm-meters	075 °F	quarterly	grab	quarterly

SAMPLING LOCATION: at the wellhead as shown in Attachment C.

^{*}The limitation on wellhead pressure serves to prevent confining-formation fracturing. This limitation was calculated using the following formula: (.8 psi/ft - (0.433 psi/ft (specific gravity))) x depth. The maximum wellhead pressure is dependent upon depth and specific gravity of the injected fluid. The Dundee Limestone at 3707 feet was used as the depth and an anticipated specific gravity of 1.27 was used for the injected fluid.

^{**}Chemical composition analyses shall include, but not be limited to, the following: Sodium, Calcium, Magnesium, Barium, Total Iron, Chloride, Sulfate, Carbonate, Bicarbonate and Sulfide.



EPA BRINE WATER ANALYSIS

DATE:

June 1, 1985

SUBMITTED ON:

May 24, 1985

LOCATION:

F.E. Beulter #2 P.N. 04741

Formation: Dundee

COMPANY:

Jack Long

Specific Gravity

1.220

PH

5.44

Chlorides

193,000 Mg/L

Total Hardness (CaCO3)

126,000 Mg/L

Total Iron

5.3 Mg/L

Bicarbonate

56 Mg/L

Barium

NIL

Calcium

40,300 Mg/L

Magnesium

6,100 Mg/L

Sodium

62,400 Mg/L

Sulfide

NIL

Sulfate

160 Mg/L

Total Dissolved Solids

(Calculated)

302,000 Mg/L

Southern Petroleum Laboratories

ATTACHMENT F

١

		ν .		* -				
	Year	M	onth		MI-073-2D-0009 Page F-2 of 4			
U.			AGENCY MONTHLY MONITORING REPORT INJECTION WELLS					
UIC PER	MIT NUMBER		Please complete and submit this report at the end of each month. This report must be postmarked no later than the 10th day of the following month.					
		•	check one	·> <u>-</u>				
OPERATO	R NAME			EOR	2MD H2			
ADDRESS			WELL NAME		·			
CITY/ST	ATE/ZIP		WELL COUNTY	Qualify processes of the shifter Start Democratic				
(AREA C	CODE) PHONE		•					
		MONTHLY RE	QUIREMENTS					
WEEK & DATE	INJECTION PRES. (psig)	ANNULUS PRE (psig)	ES. FLOW (Barrels	. 1	CHMHULATIVE VOLIME (Rarrels)			
1		· · · · · · · · · · · · · · · · · · ·						
2				reference general physical and the Market William (1988) and the	ana, agrapynym i parithir nejspellywdawa i rechtladd attention tottom tottom till retireddolfra			
3								
4	,				and the complete transport of the Assault and the Constitution of			
5					 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx			
AVERAGE HIGHEST	4				XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX			
LOWEST		de la company de la constitución		onnegado es dil cisti del più di little cari es presente di l'inference	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX			
VALUE	. Consider of Indos	tad Fluids:		niteratych Candipellir Ary Geral Condites (ch	1 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4			
Specifi	c Gravity of Injec	CERTIFI	CATION					
with th on my i mation,	e information subm nquiry of those in I believe that th	ty of law th itted in thi dividuals im e information t penalties	at I have persons document and mediately responsible true, accuracy for submitting	all attac onsible fo orate, and false inf				
	IN OFFICIAL TITLE type or print)	S	IGNATURE	DATE SIGNED				

Year	(Warter		
U. S. ENVIRONMENTAL PROTECTI FOR CLASS	ON AGENCY QUARTERL II INJECTION WELL	Y MONITOPING REPO	RT MI-073-2D-0009 Page F-3 of 4
UJC PERMIT NUMBER	the end on the postma	mplete and submit f each quarter. rked no later tha llowing months:	This report must
			er-end of 3rd quarter ry-end of 4th quarter
OPERATOR NAME	check one	>	D HS
ADDRESS		approximate and the contract of the contract o	
CITY/STATE/ZIP		ITY.	
(AREA CODE) PHONE	Alliphicates and the same and t		
- August	TOLV BEALISDEWENTE		\$
Chalade and transfer and transf	ERLY REQUIREMENTS	•	
Attach the actual laboratory as	nalysis of the foll	lowing parameters:	
Total Dissolved Solids: in par pH: no units Resistivity: in ohm - meters a	at 75° Farenheit	om)	
Chemical Composition of Inject Sodium: in ppm	ed Fluids:	Sulfate: in pp	TI.
Calcium: in ppm		Carbonate: in	ppm
Magnesium: in ppm		Bicarbonate: in Sulfide: in pp	
Barium: in ppm Iron (total): in ppm		Other Chemicals	
Chloride: in ppm		. Went gremied	
Comments:			
Date of Sampling:			n de de la companya de la compa
Sample Location:			
â.	ERTIFICATION		
I certify under the penalty of with the information submitted on my inquiry of those individuation, I believe that the int that there are significant per the possibility of fine and in	I in this document Juals immediately r Tormation is true, nalties for submitt	and all attachment esponsible for obsecurate, and consing false informations.	its and that, hased btaining the infor- uplete. I am aware bition, including
NAME AND OFFICIAL TITLE (please type or print)	SIGNATURE	agattillissenin etillitätä kinitä kentikun etim etamidapunturuna _{n er} engalunturunajan eta sepanaan	DATE SIGNED

Maryonia	- Parketin				-		Service Service		one and an order	UNITEDS	TATES	ENVIRONME	WTAL PR	OTECTION AG	ENCY			
9		D	Λ								•	WASHINGTO	N. DC 20	460		MI-073-2D-0009		
SEPA NAME AND ADDRESS OF PERMITTEE								odiana ina proiippi	A TO STORY WATER TO STORY WITH THE STORY WATER TO STORY WITH THE STORY WATER TO STORY WITH THE STORY WATER TO STORY WATER TO STORY WITH THE STORY WATER TO S		WELL REWORK RECORD				Page F-4 of 4			
NAM	AE AP	ND AC	DRES	S OF	PERI	MITTE	ŧ					- !	HAME	AND ADDRESS	S OF CONTRACTOR			
												!				· · · · · · · · · · · · · · · · · · ·		
								ı İ								. · :		
Viencus III.								6 . 4. 1	***************************************	STAT	Ē	COUNTY	2-1			PERMIT NUMBER		
LOCATE WELL AND OUTLINE UNIT ON SECTION PLAT — 840 ACRES										<u> </u>	····				yangayan iying Badayy, wang mulia Marakkan Marakkan Marakkan Marakkan Marakkan Marakkan Marakkan Marakkan Marak			
N								SURF		CATION DES	-			••				
ĩ	_	1	T	ì	_			1	l	LOCA		OF LL IN TWO D	A OF	ويرادي والمتالية والمتالية والمتالية والمتالية		OWNSHIP RANGE TER SECTION AND DRILLING UNIT		
l	i					Ļ	<u> </u>	-		1	riace							
[1		1				<u> </u>	1				ft, from	(N/S)	Line of quar	ter s ec tion			
ſ			Ţ				Γ.	T		and				ne of quarter a	ection	•		
-						Ļ	 	+- -			WEL	L ACTIVITY		Total Depth	Before Rework	TYPE OF PERMIT		
w						 	 	ļ	ŧ			hsposal ed Racover				C Individual		
			1			! 	1	1				arbon Store		Total Depth	After Rework	Number of Wells		
ľ			- -		-	<u> </u>		1	1							-		
Control Spinson	 		i		<u> </u>	ř-	- -	-	ł	"	A ezee.	isme		Data Mamo	rk Commenced	Well Number		
		لـــا	Ĺ		-	L	<u>L</u> .	<u>L</u>						Date Rewo	rk Completed	-		
	-		-			1	1	1]	1								
				4	•													
-		girayan da							Managhari Managhari	WEIL	CAEIA	IC BECOB	n _ ac	FORE REW	08 Y			
·) នាក់ខ្ម		-	- T			Cem		CMSIII	1	Periorano		T	Acid or Fracture		
	\$128	***************************************	1	Des	חום		124-7 <u>111</u> -111	Sacas	- T	Tvo		From		70	1	Tresment Record		
		*ab-14/01ai000	T			一	**************************************					1			l	and an extension of the second se		
										,								
سوننده،	n,51/4/07-			- Of east of print	enterentere						-tu-wiography			- Charles and the same of the				
**********		***********			·		-0,700 ₃ ,	gangjimma.				<u> </u>			<u> </u>	Parantara mendebana and termina mendapa tahan terminah parantara panaman terminah termina penjangan penjangan		
- Acceptions	opension,				and Proper							2222	<u> </u>					
				in-Ti			AAEL	LCA	Com		U - A	LIEWHEN	Parlarain		ons and Changes (Acid or Fracture		
	Size	on deputies the	Baing I	n _a	pih	-	enterpolitica de la constanta	Sacta		Type From			1 4110141	7118 70	-{	Freetment Record		
	6.00		Ť					500.15				1						
	nddinasih		1		- WALLEY			guta-zw	ĺ			1		•		Management of annual comment of the principles o		
								1										
	anthroppi,													a Company of the Comp				
									لـــّـــ			<u> </u>						
		annin (approximate)								***************************************		1						
							_		-	IN DETA				***************************************	WIRE LINE LOGS.			
Mary Cond	TATION IN THE		USE	AU	ווויט	UNA	r su	6123	ir ME	ESSAR				Log Ty	ye s	Logged Intervals		
	············	<u> </u>	and the state of t	(Carrellanian	neric Principal	naminings (Proc.)		***************************************	description in the second	-mossis-allisatoriii	ні по Максанції, п	***************************************						
	tananta,	**************************************	m expression or	urou ·····				nter agrippi (della riversa)	·	di Dyanganon manya	eternikas/raia as				and the second s			
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,																
	terretrii (t	estating process				900Q3400A012-		ð	-									
					٠							CERTIF	ICATI	ON	•			
			certi	ilv c	ınde	er th	ne p	enal	ty of	aw tha	i I ha	ve persor	nally e	camined a	nd am familiar	with the information		
				•					•				-			of those individuals		
															• •	ion is true, accurate.		
					•		•				_					formation, including		
												(Rel. 40 (-					
		•	٠ احتي			, -								•				
-			99.4			<u> </u>					1 8.5	AI A 91 100			and the state of t	247 0474		
NAME AND OFFICIAL TITLE (Please 1/pp or print) SIGNATU									ni)		1 316	MAIUME				DATE SIGNED		